

1 Conceptual Introduction

Since computers typically use binary internally whereas we as humans tend to use base 10, we have come up with some representation schemes to easily convert between our human notion of numbers and the computer's. Here are some of the most common ones:

Unsigned Numbers

If we have an n -digit unsigned numeral $d_{n-1}d_{n-2}\cdots d_0$ in radix (or base) r , then the value of that numeral is

$$\sum_{i=0}^{n-1} r^i d_i,$$

which is just fancy notation to say that instead of a 10's or 100's place we have an r 's or r^2 's place. For the three radices binary, decimal, and hex, we just let r be 2, 10, and 16, respectively.

Signed Numbers

Unsigned binary numbers work for natural numbers, but many calculations use negative numbers as well. To deal with this, a number of different schemes have been used to represent signed numbers. Here are two common schemes:

Two's Complement:

(a) We can write the value of an n -digit two's complement number as

$$\sum_{i=0}^{n-2} 2^i d_i - 2^{n-1} d_{n-1}.$$

(b) Negative numbers will have a 1 as their most significant bit (MSB). Plugging in $d_{n-1} = 1$ to the formula above gets us

$$\sum_{i=0}^{n-2} 2^i d_i - 2^{n-1}.$$

(c) Meanwhile, positive numbers will have a 0 as their MSB. Plugging in $d_{n-1} = 0$ gets us

$$\sum_{i=0}^{n-2} 2^i d_i,$$

which is very similar to unsigned numbers.

- (d) To negate a two's complement number: flip all the bits and add 1.
- (e) Addition is exactly the same as with an unsigned number.
- (f) Only one 0, and it's located at 0b0.

Biased Representation:

- (a) The number line is shifted so that the smallest number we want to be representable would be 0b0...0.
- (b) To find out what the represented number is, read the representation as if it was an unsigned number, then add the bias.
- (c) We can shift to any arbitrary bias we want to suit our needs. To represent (nearly) as much negative numbers as positive, a commonly-used bias for N bits is $-(2^{N-1} - 1)$.

2 Precheck: Number Representation

- 2.1

 Depending on the context, the same sequence of bits may represent different things.
- 2.2

 It is possible to get an overflow error in Two's Complement when adding numbers of opposite signs.
- 2.3

 If you interpret an n -bit Two's complement number as an unsigned number, negative numbers would be smaller than positive numbers.
- 2.4

 If you interpret an n -bit Bias notation number as an unsigned number (assume there are negative numbers for the given bias), negative numbers would be smaller than positive numbers.
- 2.5

 We can represent fractions and decimals in our given number representation formats (unsigned, biased, and Two's Complement).